


FAILURE DETECTION DEVICE FOR BATTERY SET

Patent number: JP9015311
Publication date: 1997-01-17
Inventor: MURATA SHINICHI
Applicant: JAPAN STORAGE BATTERY CO LTD
Classification:
- international: G01R19/165; G01R31/36; H01M10/42; H01M10/48;
G01R19/165; G01R31/36; H01M10/42; (IPC1-7): G01R31/36;
G01R19/165; H01M10/42; H01M10/48
- european:
Application number: JP19950183393 19950626
Priority number(s): JP19950183393 19950626

Report a data error here

Abstract of JP9015311

PURPOSE: To provide a failure detection device for a battery set which surely detects failure caused by over discharge, etc., without affected by variability in terminal voltage due to deterioration of a cell at charging/discharging by measuring the terminal voltage of module battery, more than two minutes after main charge/discharge of a battery set 1 was finished, when the terminal voltage of each cell is stable. **CONSTITUTION:** A measuring part 6a, measuring terminal voltage of each module battery 2 when more than two minutes passed after main charge/discharge of a battery set 1 was finished, is provided to a detection unit 6. And an estimation part 6b which finds an average value or a maximum value of the terminal voltage, used as reference voltage, is provided. And further, a judgment part 6c, which judges it as failure when difference between the reference voltage and each terminal voltage is higher than 1V, is provided.

Data supplied from the *esp@cenet* database - Worldwide